

Product Update

March 2009



Now Available

ProPress® Tailpiece C x F Union



Features

- CSA Approved
- UPC Approved
- NSF 61
- Temperature Range:
0°F - 250°F
- Max. Operating Pressure:
200 PSI
- EPDM Sealing Element

Viega introduces Tailpiece C X F Unions into its ProPress line. The addition of the Tailpiece C x F Unions with BSP threads, commonly called "straight threads," allows connections to mixing valves, diverter valves and water meters with fewer fittings.

The Tailpiece nut on sizes 3/4" x 1" and 1" x 1-1/4" is drilled for a seal wire. The 3/4" x 1" Tailpiece will connect to either 5/8" or 3/4" meters. The 1" x 1-1/4" Tailpiece will connect to 1" meters.

The Tailpiece C x F Unions use Viega's Press end technology, eliminating the need to thread or solder connections. The ProPress copper joining system is the fast and easy way to install copper systems. This product introduction compliments the existing ProPress line, which includes over 550 fittings.

Made of the finest quality copper material, the Tailpiece C x F Unions incorporate Viega's patented Smart Connect feature. The Smart Connect feature is the fast and easy way for installers to identify unpressed connections during pressure testing.

Stock Code	Size	List Price
77753	1/2" x 1"	16.50
77758	3/4" x 1"	24.79
77763	1" x 1"	34.89

Viega • 1-800-976-9819 • www.viega.com • service@viega.com